



**P.T. ETERNAL BUANA CHEMICAL INDUSTRIES**  
MANUFACTURER AND SUPPLIER OF SYNTHETIC RESIN & PLASTICIZERS

BARCLAYS HOUSE 7<sup>TH</sup> FLOOR, Jl Jend Sudirman Kav. 22-23 JAKARTA 12920  
Telp. 62-21-5712998, Fax 62-21-5712678  
Website: www.royalchemie.com

No. : EBCI/MSDS/4034  
Issue date : July 06, 2001  
Rev. no. : -  
Rev. date : -  
Page no. : 1 of 3

## MATERIAL SAFETY DATA SHEET

### I. PRODUCT IDENTIFICATION

Trade Name	: EBL – 6800
Chemical Name	: Vinyl Baloon
Synonyms	: None
Molecular Formula	: N/A
Chemical Family	: Vinyl acrylic solution

### II. INFORMATION ON INGREDIENT

Solvent	: 35 %
Polymer Type	: Vinyl acrylic Copolymer
Free Monomer	: 0.5 % max.
Others	: -

### III. HAZARDS IDENTIFICATION

Color	: Clear solution
Odor	: Ethyl acetat
Effect of over exposure	: Contact with eyes may cause minor temporary irritation.
Emergency and first aid procedures	: Flush eyes with plenty amount of water for a minimum of 15 minutes. If irritation develops, consult a Physician.

### IV. FIRST AID MEASURES

First aid procedures - eyes	: Immediately rinse with running water for 15 minutes. Get medical attention, if irritation develops.
First aid procedures – ingestion	: Dilute with water if swallowed.
First aid procedures – inhalation	: Remove to fresh air. If not breathing gives artificial respiration, preferably mouth to mouth. If breathing is difficult, give oxygen and seek prompt medical attention.

Note to Physician :

Toxicology studies have shown similar material to be of very low acute toxicity. There is no specific antidote. Treatment of over exposure should be directed at the control of symptoms and the clinical conditions.



**P.T. ETERNAL BUANA CHEMICAL INDUSTRIES**  
MANUFACTURER AND SUPPLIER OF SYNTHETIC RESIN & PLASTICIZERS

BARCLAYS HOUSE 7<sup>TH</sup> FLOOR, Jl Jend Sudirman Kav. 22-23 JAKARTA 12920  
Telp. 62-21-5712998, Fax 62-21-5712678  
Website: www.royalchemie.com

No. : EBCI/MSDS/4034  
Issue date : July 06, 2001  
Rev. no. : -  
Rev. date : -  
Page no. : 2 of 3

## V. FIRE FIGHTING MEASURES

- + Flash Point : ( See physical properties )
- + Flammable Limits in Air, % by volume : Unknown
- + Lower : Undetermined Upper : Undetermined
- + Extinguishing Media : Use carbon dioxide or dry chemical on small fires. Use foam (alcohol, polymer or ordinary) and water spray for large fires.
- + Special Fire Fighting Procedures : Self – contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.

## VI. ACCIDENTAL RELEASE MEASURES

Action to take spills : (Use appropriate safety equipment).  
Use absorbent material to collect and contain for disposal. Contain large spills and pump into suitable tank. Wash the area with water and thoroughly rinse.

## VII. STORAGE AND HANDLING

Store in well ventilated areas at temperature below 120 °F. Keep container tightly closed. Do not store or consume food, drink, or tobacco in area where they may become contaminated with this material.

## VIII. PERSONAL PROTECTION

- + Ventilation :
  - 1. Local exhaust : Should be needed
  - 2. Respiratory protection (type) : Canister for organic vapors (i.e. type GMA from Mine Safety Appliance Co.)
- + Protective Clothing : clean, body-covering clothing. In addition, rubber gloves, boots and apron, depending upon the exposure likely, or as required by your company).
- + Eye Protection : Safety goggles recommended.

## IX. PHYSICAL PROPERTIES

- + Solubility in solvent : Soluble in ethyl acetate
- + Specific Gravity : 1.00 – 1.10
- + Volatiles, % : > 1
- + Appearance : Clear solution
- + Odour : Ethyl acetate
- + Flash Point, PMCC°F : 24 and 40



**P.T. ETERNAL BUANA CHEMICAL INDUSTRIES**  
MANUFACTURER AND SUPPLIER OF SYNTHETIC RESIN & PLASTICIZERS

BARCLAYS HOUSE 7<sup>TH</sup> FLOOR, Jl Jend Sudirman Kav. 22-23 JAKARTA 12920  
Telp. 62-21-5712998, Fax 62-21-5712678  
Website: www.royalchemie.com

No. : EBCI/MSDS/4034  
Issue date : July 06, 2001  
Rev. no. : -  
Rev. date : -  
Page no. : 3 of 3

## X. STABILITY AND REACTIVITY

- Stability : Stable
- Hazardous Decomposition Products : Thermal decomposition may produce carbon mono/ dioxides.
- Hazardous polymerization : Will not occur
- Condition to avoid : See above statement

## XI. TOXICOLOGICAL INFORMATION

No applicable data for this section.

## XII. ECOLOGICAL INFORMATION

No applicable data for this section.

## XIII. DISPOSAL CONSIDERATION

- Disposal Method : All local, state and federal regulation concerning health and pollution should be reviewed to determine approved disposal procedures.
- Do not discharge into waterways or sewer system.

## XIV. TRANSPORTATION INFORMATION

Not regulated by the department of transportation.

## XV. REGULATORY INFORMATION

This product contains one or more chemicals known to cause cancer.  
No additional information.

## XVI. OTHER INFORMATION

- Effect of over exposure : Contact with eyes may cause irritation
- Emergency and first aid procedures : Flush eyes with plenty amount of water for a minimum of 15 minutes.  
If irritation develops, consult a Physician.

This above data and information apply to the product as such and confirming to specifications given by Eternal Buana Chemical Industries. While the information is believed to be correct, Continental shall in no event be responsible for any damages what so ever, directly or indirectly resulting from the publication or use of or reliance upon data contained here in. Users are advised of possible additional hazard when the product is used in applications for which it was not intended. This sheet only be used and reproduced for prevention and security purposes