



TECHNICAL DATA SHEET

EBL - 5433

I. DESCRIPTION

EBL - 5433 is formaldehyde free acrylic adhesive that designed for manufacture of flexible laminates that used for food and beverage packaging.

II. PERFORMANCE

- One part component.
- Fast line speed.
- High adhesion on a wide variety of films.
- Low odour.
- Excellent film clarity.

III. SPECIFICATION

- Non-Volatile (150 °C, 15 mins) : 41 ± 1 %
- Viscosity at 30 °C, cPs : max.50
(Brookfield LVT, No.1/60 rpm)
- pH Value : 6.5 - 7.5
- Density, lbs/US gallon : 8.35 - 8.45
- Toxicity : Non Toxic

IV. STANDARD PACKING

150 kgs in open head plastic drums packed inside with 2 liners of HDPE plastic bags.

V. STORAGE

- Avoid direct sunlight.
- Keep the plastic bags for remaining stock tightly sealed to avoid skinning.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.