



TECHNICAL DATA SHEET

EBL - 5502 HV

I. DESCRIPTION

EBL - 5502 HV is water based synthetic resin of Poly vinyl Acrylic Terpolymer designed for Pressure Sensitive Adhesive.

II. PERFORMANCE

- High initial tack.
- Good adhesion.
- Moderate cohesion.

III. SPECIFICATION

- Non-Volatile (150 °C, 15 mins) : 60 ± 1 %
- Viscosity at 30 °C, cPs : 10,000 - 35,000
(Brookfield LVT, No.4/12 rpm)
- pH Value : 4 - 5
- Appearance : Milky White
- Density, lbs./US gallon : 8.7 - 9.0
- Toxicity : Non Toxic

IV. STANDARD PACKING

210 kgs in open head metal drums packed inside with 2 liners of HDPE plastic bags.

V. STORAGE

- Avoid direct sunlight.
- Keep the plastic bags for remaining stock tightly sealed to avoid skinning.
- Storage life is 6 months after delivery.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.