



TECHNICAL DATA SHEET

EBL - 5602 LS

I. DESCRIPTION

EBL - 5602 LS is a milky white synthetic emulsion of Polyvinyl Acetate Homopolymer specially designed as wood working adhesive and also paper overlay adhesive.

II. PERFORMANCE

- High initial tack.
- Excellent bonding strength.
- Easily diluted with water.

III. SPECIFICATION

- Non-Volatile (150 °C, 15 mins) : 36 ± 1.5 %
- Viscosity at 30 °C, cPs, : 10,000 - 20,000
(Brookfield RVT, No.6/10 rpm)
- pH Value : 3.5 - 5.0
- Appearance : Milky White
- Density, lbs./US gallon : 8.60 - 8.80
- Toxicity : Non toxic

IV. STANDARD PACKING

210 kgs in open head metal drums packed inside with 2 liners of HDPE plastic bags.

V. STORAGE

- Avoid direct sunlight.
- Keep the plastic bags for remaining stock tightly sealed to avoid skinning.
- Storage life is 6 months after delivery.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.