



## TECHNICAL DATA SHEET

### EBL - 5895

#### I. DESCRIPTION

EBL - 5895 is an aqueous acrylic emulsion polymer white pressure sensitive properties especially designed for OPP carton - sealing tape.

#### II. PERFORMANCE

- Outstanding instantaneous cardboard adhesion and fiber-tear.
- Excellent shear resistance.
- Excellent loop tack and quick grab.
- Excellent humidity resistance.
- Excellent tack at low and high temperatures.
- Water-white color and good clarity.
- Ultraviolet (UV) and elevated temperature stability.
- Ready-to-coat using knife-over-roll, Myers rod or nip-fed 3-roll reverse roll coater.

#### III. SPECIFICATION

- Non-Volatile (150 °C, 15 mins) : 55.5 - 56.0 %
- Viscosity at 30 °C, cPs : 180 - 230  
(Brookfield LVT, No.2/30 rpm)
- pH Value : 8.5 - 9.0
- Appearance : Milky White
- Density, lbs./US gallon : 8.50 - 8.60
- Toxicity : Non Toxic

#### IV. STANDARD PACKING

200 kgs in open head metal drums packed inside with 2 liners of HDPE plastic bags.

#### V. STORAGE

- Avoid direct sunlight.
- Keep the plastic bags for remaining stock tightly sealed to avoid skinning.
- Storage life is 6 months after delivery.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.



## TECHNICAL DATA SHEET

---

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

---

PT. ETERNAL BUANA CHEMICAL INDUSTRIES  
Tel. (62-21) 571 2998, Fax : (61-21) 571 2678

Issue date : Jan 10, 1996  
Revised no : 01  
Revised date : June 01, 2001