



TECHNICAL DATA SHEET

EBA 1436 - 60

I. DESCRIPTION

EBA 1436 - 60 is a short oil alkyd resin based on Tall Oil Fatty Acid (TOFA) with excellent hardness and fast drying time. It can be used for NC Lacquers, PU, acid curing and baking finishes.

II. PERFORMANCE

- Fast dry.
- Good adhesion.
- Excellent Hardness.
- Good water resistance.

III. SUGGESTED USES

- Amino - Alkyd acid curing.
- NC lacquer.
- Low temperature baking enamel.

IV. SPECIFICATION

- Non-Volatile (150 °C, 15 mins) : 60 ± 2 %
- Viscosity (25 °C, Gardner-Holdt) : Z2 - Z4
- Acid Value (mg KOH/g solid) : max. 20
- Color (Gardner-Holdt), : max. 5
- Appearance : clean & clear
- Specific Gravity (25 °C) : ca. 1.033
- OH Value (mg KOH/g solid) : ca. 100

V. STANDARD PACKING

210 kgs in metal drums.

VI. STORAGE AND HANDLING

- Store in proper warehouse.
- Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.