

**TECHNICAL DATA SHEET****EBINO 8121 - 65****I. DESCRIPTION**

EBINO 8121 - 65 is Iso-butylated urea formaldehyde resin. It is mainly used for wood finishes in combination with short oil alkyd resin. It is designed to give low odor resin and higher viscosity.

II. PERFORMANCE

- Fast cure.
- Gloss.
- Good adhesion.
- Low free formaldehyde.

III. SUGGESTED USES

- Acid curing amino – alkyd.
- General industrial stoving enamel.

IV. SPECIFICATION

- Non-Volatile (150 °C, 15 mins) : 65 ± 2 %
- Viscosity (25 °C, Gardner - Holdt) : Z2 - Z4
- Acid Value (mg KOH/g solid) : maximum 4
- Color (Gardner-Holdt) : maximum 1
- Appearance : clean & clear
- Free formaldehyde : maximum 0.5 %

V. STANDARD PACKING

210 kgs in metal drums.

VI. STORAGE AND HANDLING

- Store in proper warehouse.
- Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.