



TECHNICAL DATA SHEET

EBL - 3000

I. DESCRIPTION

EBL - 3000 is an all acrylic emulsion polymer, especially designed for making high performance exterior paint and roof paint.

II. PERFORMANCE

- Much better adhesion over old oil paint and oil based primers.
- Greatly improved adhesion to masonry walls.
- High-gloss film.
- Good weatherability.
- Excellent water resistance.
- Outstanding alkali resistance.

III. SPECIFICATION

- Non-Volatile (150 °C, 15 mins) : 48 ± 1 %
- Viscosity at 30 °C, cPs : 250 - 700
(Brookfield LVT, No.2/30 rpm)
- pH Value : 9 - 10
- Appearance : Milky white - Bluish
- Particle size, Mastersizer/E micron : 0.2
- Ionic Nature : Anionic
- Surface tension, dyne/cm : 41
- MFFT, °C : + 31

IV. STANDARD PACKING

200 kgs in open head metal drums packed inside with 2 liners of HDPE plastic bags.

V. STORAGE

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.



TECHNICAL DATA SHEET

- Avoid direct sunlight.
- Keep the plastic bags for remaining stock tightly sealed to avoid skinning.
- Storage life is 6 months after delivery.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

PT. ETERNAL BUANA CHEMICAL INDUSTRIES
Tel. (62-21) 571 2998, Fax : (61-21) 571 2678

Issue date : Jan 10, 1996
Revised no : 01
Revised date : June 01, 2001