



TECHNICAL DATA SHEET

EBL - 3103

I. DESCRIPTION

EBL – 3103 is a synthetic emulsion of Polyvinyl Acrylic Copolymer designed for interior and exterior wall paint.

II. PERFORMANCE

- More water resistance.
- Better durability.
- Medium viscosity.
- High molecular weight.

III. SPECIFICATION

- Non-Volatile (150 °C, 15 mins) : 58 ± 1 %
- Viscosity at 30 °C, cPs : 750 - 2,000
(Brookfield LVT, No.4/60 rpm)
- pH Value : 4-5
- Appearance : Milky White :
- Density, (30 °C), gr/cm³ : 1.048 - 1.066
- Particle size, Mastersizer/E micron : 0.3 - 0.4
- Theoretical Tg, °C : + 10

IV. STANDARD PACKING

200 kgs in open head metal drums packed inside with 2 liners of HDPE plastic bags.

V. STORAGE

- Avoid direct sunlight.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.



TECHNICAL DATA SHEET

- Keep the plastic bags for remaining stock tightly sealed to avoid skinning.
- Storage life is 6 months after delivery.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

PT. ETERNAL BUANA CHEMICAL INDUSTRIES
Tel. (62-21) 571 2998, Fax : (61-21) 571 2678

Issue date : Jan 10, 1996
Revised no : 01
Revised date : June 01, 2001