



TECHNICAL DATA SHEET

EBL - 3303

I. DESCRIPTION

EBL - 3303 is a Vinyl Versatate Copolymer latex specially designed for outstanding durability exterior wall paints. Paint made with EBL - 3303 showed excellent alkali resistance as well as its scrub and water resistance.

II. PERFORMANCE

- Water resistance.
- Excellent alkaly resistance.

III. SPECIFICATION

- Non-Volatile (150 °C, 15 mins) : 54 ± 1 %
- Viscosity at 30 °C, cPs : 4,000 - 6,000
(Brookfield LVT, No.4/60 rpm)
- pH Value : 4 - 5
- Appearance : Milky White
- Density, lbs./US gallon : 8.70
- Mechanical stability : Excellent
- Chemical stability : Excellent
- Toxicity : Non toxic
- Theoretical Tg, °C : + 8.5

IV. STANDARD PACKING

200 kgs in open head metal drums packed inside with 2 liners of HDPE plastic bags.

V. STORAGE

- Avoid direct sunlight.
- Keep the plastic bags for remaining stock tightly sealed to avoid skinning.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.



TECHNICAL DATA SHEET

- Storage life is 6 months after delivery.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

PT. ETERNAL BUANA CHEMICAL INDUSTRIES
Tel. (62-21) 571 2998, Fax : (61-21) 571 2678

Issue date : Jan 10, 1996
Revised no : 01
Revised date : June 01, 2001